



## The Sullair 260 Portable Air Compressor

260 cfm at 100 psig ■ 7.4 m<sup>3</sup>/min at 7 bar

- Rotary screw compressor
- Removable modular canopy
- Wheel bearing grease fittings
- Large tool box compartment
- Weather proof instrument panel
- Protective shutdown switches
- Idle warm-up valve
- SSAM – Shutdown System and Annunciation Module
- Rocker type start switch
- Fuel/Water separator
- Two-stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Galvanneal sheet metal
- Durable powder coat finish
- Wide track
- Recessed tail lights
- Rear bumper

  
**SULLAIR**<sup>®</sup>  
Always air. Always there.<sup>®</sup>



**Instrument Panel Featuring SSAM**  
Shutdown System & Annunciation Module.



**Wheel Bearing Grease Fitting**  
Offers convenient wheel bearing lubrication thru zerk fittings.



**Rotary Screw Design**  
by Sullair, the pioneer in rotary screw technology.



**Sullair AWF Compressor Fluid**  
Improved hot and cold weather lubrication. Longer compressor fluid life. Extended air end warranty.

**Designed for Total Accessibility and Reliability**

**Rotary Screw Compressor**

**Ample Service Doors**

- Large service doors provide access to fuel tank, engine, compressor and tool compartment
- Service doors feature non-rusting hinges, with built-in weather strip and stainless steel T-type door retainers
- Rear service panel provides access to side by side compressor fluid cooler and engine radiator
- Serviceable components within easy reach
- Routine maintenance is simplified
- Reduced downtime and service cost

**Modular Canopy and Frame**

- Canopy easily removed in one piece for major service
- Modular design reduces replacement costs
- Exposed, single point lifting bail

**0 to 100% Capacity Control**

- Pneumatic inlet valve and unloaded starting

**Highway Towable Running Gear**

- 3" square drawbar
- Transport security chains
- Heavy duty leaf spring suspension
- Wide track stability

**Large Tool Box**

**Instrument Panel**

- Hinged, padlockable cover
- Mechanical air pressure gauge and hourmeter
- Rocker type engine start switch
- Idle warm-up switch

**SSAM—Shutdown System & Annunciation Module**

- Shutdown with annunciator light for high compressor temperature, high engine coolant temperature, low engine oil pressure and engine under-speed

**Durable, Baked-on Powder Coat Finish**

**Two-Stage Dry Type Air Filters**

- Separate filters for engine and compressor

**Tier 4 Interim / Stage III B Emissions Compliant Engines\***

**Air End Warranty**

- 2-year standard warranty
- 5-year or 10,000-hour warranty when continuously serviced at the recommended intervals with Sullair AWF Compressor Fluid and filters

**Quiet Operation**

- Meets US EPA sound requirements of 76 dBA @ 7 meters

\* CAT only.

**Customize the compressor to meet your specific requirements with Sullair's options**

Special paint  
Hose reels, single and dual  
Spark arrestor  
Fuel level gauge  
Gauge package

Tachometer  
Brakes (recommended where required by law)  
Mechanical parking brakes  
Block heater

Ball hitch  
Air filter maintenance indicators  
Air filter safety elements  
Low fuel shutdown

**SPECIFICATIONS, WEIGHTS AND DIMENSIONS—SULLAIR 260 PORTABLE COMPRESSOR**

Delivery @ Rated Pressure	Rated Pressure psig bar	Pressure Range psig bar		Designated Model	Weight ** (wet) lbs kg		Weight ** (dry) lbs kg		Length (drawbar) in mm		Length (canopy) in mm		Width in mm		Height in mm		Track Width in mm		Tire Size (load range)
		psig	bar		lbs	kg	lbs	kg	in	mm	in	mm	in	mm	in	mm	in	mm	
260 acfm 123 l/s 7.4 m <sup>3</sup> /min	100 7	80–125	5.5–8.5	2-Wheel	2840	1288	2595	1177	143.3	3640	85.1	2162	65.4	1661	59.9	1522	55	1397	205/75D15
					Less Running Gear	2585	1173	2340	1061	–	–	85.1	2162	47.5	1207	49.0	1245	–	–

  

Engine Make	Engine Type	Engine Model	Displacement in <sup>3</sup> cc		Cylinders	Bore and Stroke in mm		Rated Speed rpm	Rated Power hp kW	
Caterpillar	Diesel	C3.4 (Tier 4 Interim)	201	3272	4	3.70 x 4.72	94 x 120	2500	74	56
John Deere	Diesel	5030TF270 (Tier 2)	186	3028	4	3.39 x 4.13	86 x 105	2500	82	61

John Deere model available outside North America and the EU Countries

Capacity per CAGI/PNEUROP PN2CPTC3. (Annex D to ISO 1217)

\*\* Weights are for John Deere. For Caterpillar, deduct 80 lbs (37 kg).

**ALL COMPRESSORS ARE BACKED WITH FAST DELIVERY, INSTALLATION AND A RANGE OF SERVICE SOLUTIONS**

SULLAIR AUSTRALIA PTY LTD ABN 68 006 732 332

324-332 Frankston-Dandenong Road, Dandenong, VIC Australia 3175

PO Box 5194, Hallam, VIC 3803 P 1300 COMPRESSOR (1300 266 773)

F +61 3 9703 9053 facebook.com/SullairAustralia

sales@sullair.com.au SULLAIR.COM.AU

